

KM-201BAH 09/15/17 Item # 13238

Item #:	_
Project:	_
Qty:	_
AIA#:	_

WxDxH 24" x 28" x 39" * *including 6" legs

KM-201BAH ★ Air-Cooled Shown

















Features

- Individual crescent cube
- Stainless steel evaporator
- ► CycleSaver™ design \(\text{CYCLESAVER} \)



- Up to 215 lbs. of ice production per 24 hours
- Built-in storage capacity of 2.7ft³/80 lbs.*
- · Durable stainless steel exterior
- Front in, front out airflow
- · Ice bin opening is ADA compliant
- EverCheck™ alert system
- Removable air filter (Air-cooled model only)
- · R-404A Refrigerant

Warranty:


3 Year Parts & Labor on entire machine. 5 Year Parts & Labor on Evaporator. 5 Year Parts on Compressor; air-cooled condenser coil.

Valid in United States, Canada, Puerto Rico and U.S. Territories. Contact factory for warranty in other countries.

*Rated in accordance with AHRI Standard 820(I-P). Capacity based on 100% of total volume x 30 lb/ft3 average density of ice.

			ICE PRODUCTION			WATER USAGE		ELECTRICAL							
	Condenser	Model	Air / Water Temp Lbs. per 24 hours 70°/ 50°F 90°/ 70°F		Per (Lbs.	Cycle Cubes	Potable Gal. per 100 lbs. 90°/ 70°F			Max. Fuse Size or HACR Circuit Breaker	Amperage	Voltage	Heat Rejection BTU/hr.	Shipping Weight	ENERGY STAR®
	Air-Cooled	KM-201BAH	201	165	4.0	182	22.0	N/A	7.5	15A	6.1A	115V/60/1	3,450	177 lbs.	*

KM Cube Dimensions*



* approximate size in inches, image not to scale

Operating Limits

· Ambient Temp Range 45 - 100°F Water Temp Range 45 - 90°F · Water Pressure 10 - 113 PSIG · Voltage Range 104 - 127V

Service

· Allow enough space at rear for water supply and drain connections. Allow at least 2" (5 cm) on right side for proper air circulation and at least 0.6" (15 mm) clearance at top for service/maintenance.

Plumbing

- Icemaker Water Supply Line: Minimum 1/4" Nominal ID Copper Water Tubing or Equivalent
- Icemaker Drain Line: Minimum 3/4" Nominal ID Hard Pipe or Equivalent

Hoshizaki reserves the right to change specifications without notice.

Printed in the U.S.A.



