

KMS-1401MLJ 03/31/2017 Item # 13289

WxDxH 30" x 24" x 28"

Installation Dimension* **SRK-14J / SRK-14J3** 523/8" x 191/2" x 43"

*Dimensions include legs

Actual Dimension SRK-14J / SRK-14J3 50" x 17" x 28"

KMS-1401MLJ

Remote Air-Cooled Shown on optional Lancer 30" Dispenser

















Item #: Project: _ Qty:

Features

ΔΙΔ#٠

- Individual crescent cube
- Stainless steel evaporator
- ► CycleSaverTM design \(\int \) CYCLESAVE




- Up to 1420 lbs. of ice production per 24 hours
- · Durable stainless steel exterior
- Protected by H-GUARD Plus F-GUARD **Antimicrobial Agent**
- EverCheck™ alert system
- · Less heat in the kitchen
- · Minimized noise
- · CFC / HFC Free Foam
- R-404A Refrigerant
- Not recommmended for side-by-side application

3 Year Parts & Labor on entire machine. 5 Year Parts & Labor on Evaporator. 5 Year Parts on Compressor; air-cooled condenser coil.

Valid in United States, Canada, Puerto Rico and U.S. Territories. Contact factory for warranty in other countries.

	ICE PRODUCTION				WATER USAGE		ELECTRICAL							
Condenser	Model	Air / Water Temp Lbs. per 24 hours 70°/ 50°F 90°/ 70°F		rs Fei	Cycle Cubes	Potable Gal. per 100 90°/ 70°F		kWh Used per 100 lbs. 90°/ 70°F	Max. Fuse Size or HACR Circuit Breaker	Amperage	Voltage	Heat Rejection BTU/hr.	Shipping Weight	ENERGY STAR®
Remote Air-Cooled	KMS-1401MLJ with SRK-14J	1420	128	0 25.8	1248	3 19.5	N/A	4.7	20A	13.5A	115V/60/1*	28,800	177 lbs.	
Remote Air-Cooled	KMS-1401MLJ with SRK-14J3	1400	128	0 26.7	1248	3 20.0	N/A	4.7	20A	11.5A	115V/60/1*	29,100	177 lbs.	
	LINE SETS - Pre-Charge				jed	TEMP RANGE	ELECTRICAL				* Voltage supply for KMS Ice Maker is supplied from the SRK Remote Condenser			
Condenser	Model	20' Length 35' L		35' Lengt	th 55' Length		Ambient (Outdoor Use)	Voltage Range	Max. Fuse Size or HACR Circuit Breaker	Amperage	Voltage	Heat Rejection BTU/hr.	Shipping Weight	ENERGY STAR®
Remote	SRK-14J	R404-20810** R4		R404-3581	04-35810** R40		-20 - 122°	187-253VAC	20A	13.5A	208-230V/60/1	28,800	275 lbs.	
Remote	SRK-14J3	R404-20810** R4		R404-3581	0** R	404-55810**	-20 - 122°	187-253VAC	20A	11.5A	208-230V/60/3	29,100	275 lbs.	
													* * line sets reau	uire refrigerant

KM Cube Dimensions*



* approximate size in inches, image not to scale

Operating Limits- KMS-1401MLJ

- · Ambient Temp Range
- 45 100°F 45 - 90°F
- Water Temp Range Water Pressure
- 10 113 PSIG
- Voltage Range
- 187-253V*
 - * Voltage supply for KMS Ice Maker is supplied from the SRK Remote Condensel

Service- KMS-1401MLJ

· Panels easily removed and all components accessible for service.

Plumbing- KMS-1401MLJ

- · Icemaker Water Supply Line: Minimum 3/8" Nominal ID Copper Water Tubing or Equivalent
- Icemaker Drain Line: Minimum 3/4" Nominal ID Hard Pipe or Equivalent

- Service- srk-14J(3)
 Allow 24" (61 cm) clearance in both front and rear for proper air circulation and ease of maintenance/service.
- For best performance the Remote Condenser should not be more than 33 feet above the icemaker or no more than 10 feet below it. These distances are measure from fitting to fitting.


Hoshizaki reserves the right to change specifications without notice.


Printed in the U.S.A.




SIDE VIEW









24.17" [613.8mm] 1.32" [33.5mm] 1.66" 1.66" 1.32" [33.5mm] 1.32" [33.5mm] 1.32" [33.5mm] 1.32" [30mm] 1.18" Drain 5/8" OD Pipe







SRK-14J(3) REMOTE CONDENSER

SRK-14J(3) Remote Condenser (Sold Separately)
(W x D x H) 52^{3/8} x 19^{1/2} x 43
For Use with KMS-1401MLJ(3)

